



TX-350

PROFESSIONAL FM TRANSCEIVER

- TOT
- Scan
- Voice prompt
- Battery saving function
- Low battery prompt
- Wide/narrow bandwidth selectable
- Busy channel lock
- Squelch
- Programming password
- CTCSS/ DCS
- Scrambler

Main Functions

- TOT
- Scan
- Voice prompt
- Battery saving function
- Wide/narrow bandwidth selectable
- Busy channel lock
- Squelch
- Programming password
- Low battery prompt
- CTCSS/ DCS
- Scrambler

Technical

GENERAL	Frequency range	420-450MHz
	Channel No	16
	Working voltage	3.7V
	Working temperature	-10° C~+50° C
	Antenna	high gain antenna
	Antenna Impedance	50Ω
	Dimension	109*55*32mm
TRANSMITTER	Frequency range	420-450MHz
	RF power	2W
	Modulation type	16KF 3E
	Spurious Radiation	≤7.5 μ W
	Modulation noise	<-40dB
	Modulation Distortion	<5%
	Frequency stability	5ppm
	Max Fr. Deviation	≤ ± 5KHz
	Current	≤ 1200mA
	Audio Response	+6.5~-14dB
RECEIVER	Adjacent Ch. Power	≥65dB
	Frequency range	420-450MHz
	Receiving Sensitivity	≤ 0.2 μ V
	Occupied Bandwidth	≤ 16KHz
	Selectivity	≥65dB
	Current	standby 55mA, working 150mA
	Audio response	+7~-12.5dB
Audio power output	>500m W	

Standard Accessories



Battery



Charger



Antenna



Belt Clip

MÉXICO: +52 (614) 415-2525 USA: +1 (915) 533-5119
 Colombia: +57 1 744 - 3650
 E-mail: ventas@syscom.mx
www.syscom.mx



FCC ID: 2AS4FEPCOTX-350